



SAFETY DATA SHEET

BELZONA® 3121 (MR7) SOLIDIFIER

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name BELZONA® 3121 (MR7) SOLIDIFIER

Product number SN2701

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses An emergency repair and weatherproofing system for sealing all types of roof surfaces against atmospheric attack even during adverse weather conditions. Designed for instant weatherproofing at all times of year. For industrial use only.

Uses advised against The product should not be used for purposes other than those recommended in the appropriate Instructions For Use (IFU) leaflet.

1.3. Details of the supplier of the safety data sheet

Supplier Belzona Polymerics Limited
Claro Road, Harrogate
HG1 4DS
United Kingdom
+44 1423 567641
sds@belzona.com

Manufacturer Belzona Polymerics Limited
Claro Road, Harrogate
HG1 4DS
United Kingdom
+44 1423 567641
sds@belzona.com

1.4. Emergency telephone number

Emergency telephone VelocityEHS: +1 813-248-0585

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (SI 2019 No. 720)

Physical hazards Flam. Liq. 3 - H226

Health hazards Skin Corr. 1B - H314 Eye Dam. 1 - H318 Skin Sens. 1 - H317 STOT SE 3 - H335, H336 Asp. Tox. 1 - H304

Environmental hazards Aquatic Chronic 2 - H411

Reference The full text for all hazard statements is displayed in Section 16.

2.2. Label elements

BELZONA® 3121 (MR7) SOLIDIFIER**Hazard pictograms****Signal word**

Danger

Hazard statements

H226 Flammable liquid and vapour.
 H304 May be fatal if swallowed and enters airways.
 H314 Causes severe skin burns and eye damage.
 H317 May cause an allergic skin reaction.
 H335 May cause respiratory irritation.
 H336 May cause drowsiness or dizziness.
 H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P260 Do not breathe vapours.
 P280 Wear protective gloves, protective clothing and eye protection.
 P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
 P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P310 Immediately call a POISON CENTRE or doctor.

Contains

HYDROCARBONS, C9, AROMATICS, PHENOL, METHYLSTYRENATED, 4,4'-METHYLENEBIS(CYCLOHEXANAMINE)

2.3. Other hazards

Based on information received from our suppliers no PBT or vPvB substances are intentionally added to this product.

SECTION 3: Composition/information on ingredients**3.2. Mixtures**

BENZYL ALCOHOL	12-32%
CAS number: 100-51-6	EC number: 202-859-9
Classification	
Acute Tox. 4 - H302	
Acute Tox. 4 - H332	
HYDROCARBONS, C9, AROMATICS	10-30%
CAS number: —	EC number: 918-668-5
Classification	
Flam. Liq. 3 - H226	
STOT SE 3 - H335, H336	
Asp. Tox. 1 - H304	
Aquatic Chronic 2 - H411	

BELZONA® 3121 (MR7) SOLIDIFIER

PHENOL, METHYLSTYRENATED	10-30%
CAS number: 68512-30-1	EC number: 700-960-7
Classification	
Skin Irrit. 2 - H315	
Skin Sens. 1 - H317	
Aquatic Chronic 3 - H412	
4,4'-METHYLENEBIS(CYCLOHEXANAMINE)	2-8%
CAS number: 1761-71-3	EC number: 217-168-8
Classification	
Acute Tox. 4 - H302	
Skin Corr. 1B - H314	
Eye Dam. 1 - H318	
Skin Sens. 1B - H317	
STOT RE 2 - H373	
2,4,6-tris(dimethylaminomethyl)phenol	1-5%
CAS number: 90-72-2	EC number: 202-013-9
Classification	
Skin Irrit. 2 - H315	
Eye Irrit. 2 - H319	

The full text for all hazard statements is displayed in Section 16.

Composition comments The benzene content of the hydrocarbon constituents contained within this product is significantly below the 0.1% w/w threshold and therefore, the product is not classified as a carcinogen. Related CAS No. for Hydrocarbons, C9, aromatics is 64742-95-6.

SECTION 4: First aid measures**4.1. Description of first aid measures**

General information	In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.
Inhalation	Remove to fresh air. Keep the patient warm and at rest. Give nothing by mouth. If unconscious, place in the recovery position and seek medical advice.
Ingestion	If accidentally swallowed obtain immediate medical attention. Keep at rest. Rinse mouth with plenty of water. Do NOT induce vomiting.
Skin contact	Remove contaminated clothing. Wash skin thoroughly with soap and water or use a proprietary skin cleaner. Do NOT use solvents or thinners. If irritation or inflammation persists, seek medical attention.
Eye contact	Contact lenses should be removed. Irrigate copiously with clean, fresh water for at least 15 minutes, holding the eyelids apart, and seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed

BELZONA® 3121 (MR7) SOLIDIFIER

Inhalation	Exposure to organic solvent vapours may result in adverse health effects such as irritation of the mucous membrane and the respiratory system and adverse effects on the renal and central nervous systems. Inhalation of vapour, skin absorption and ingestion may result in symptoms of central nervous system depression, such as headache, drowsiness, nausea and vomiting. Entry into the lungs following ingestion or vomiting may cause chemical pneumonitis.
Ingestion	Inadvertent ingestion of small amounts of this product through poor hygiene or cross contamination may cause irritation of mucous membranes, headache, nausea, diarrhoea, dizziness and loss of coordination.
Skin contact	Skin contact causes chemical burns. Symptoms may include pain, severe local redness and tissue damage. May cause allergic skin reaction.
Eye contact	Contact with eyes may cause severe irritation with corneal injury, which may result in permanent impairment of vision.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor None.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Use: sand, alcohol resistant foam, carbon dioxide, chemical powder, or water fog for larger fires.
Do NOT use water jet.

5.2. Special hazards arising from the substance or mixture

Hazardous combustion products In a fire, hazardous decomposition products such as smoke, carbon monoxide, carbon dioxide, oxides of nitrogen and ammonia may be produced.

5.3. Advice for firefighters

Protective actions during firefighting Fire will produce dense black smoke containing hazardous products of combustion. Exposure to decomposition products may be a hazard to health. Appropriate self-contained breathing apparatus may be required. Cool closed containers exposed to fire with water spray. Do not allow run-off from fire fighting to enter drains or watercourses.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Exclude sources of ignition and ventilate the area. Exclude non-essential personnel. Keep up-wind of spill to avoid breathing vapours. Do not get on skin or in eyes.

6.2. Environmental precautions

Environmental precautions Prevent product entering drains or sewers. If the product enters drains or sewers in large quantities, the local Water Company should be contacted immediately; in the case of contamination of streams, rivers or lakes, the appropriate National regulating agency.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Contain and collect spillages with non-combustible absorbent materials e.g. sand, earth, vermiculite, diatomaceous earth and place into a suitable labelled container. Clean surfaces down with a water and detergent mixture. Do not allow spilled product or the associated washings to enter surface water drains or watercourses.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. For waste disposal, see section 13. For information on National regulating agencies refer to Section 16.

BELZONA® 3121 (MR7) SOLIDIFIER

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions

GENERAL Keep the container tightly closed when not in use. Exclude non-essential personnel. Minimise the number of employees exposed and the duration of their exposure. Vapours may collect in the container headspace during transit or prolonged storage. Do not breathe vapour when opening the container. Where possible open containers and mix components in a well ventilated place away from the application area. Do not get on skin or in eyes. Smoking, eating and drinking should be prohibited in areas of storage and use. For personal protection see Section 8. Always keep in containers made of the same material as the supply container. FIRE/EXPLOSION The product is flammable. Exclude sources of heat, sparks and open flame. Vapours are heavier than air and may spread along floors. They may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapour with air. The product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. Good housekeeping standards and regular safe removal of waste materials will minimise the risks of spontaneous combustion and other fire hazards. Ensure emergency equipment (for fires, spills, leaks, etc.) is readily available.

Advice on general occupational hygiene

Wash at the end of each work shift and before eating, smoking and using the toilet. Ensure eye wash facilities (fountain, bottle, vials, etc.) are readily available. Do not put contaminated articles or equipment e.g. spatulas, applicators, brushes, cloths etc., into pockets. Where necessary, contaminated work clothing and shoes should be removed to prevent cross contamination of surfaces and the risk of inadvertent skin contact and ingestion.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions

Observe the label precautions. Store between 5 °C and 30 °C unless otherwise stated in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. No smoking. Prevent unauthorised access. Store separately from oxidising agents and strongly acidic materials. ENVIRONMENTAL STORAGE PRECAUTIONS Spillage, incorrect storage of chemicals or waste materials or unsuitable disposal activities can result in pollutants seeping through the soil, causing serious harm to groundwater- which is a vital source of drinking water. All wastes, especially liquid wastes, must be securely stored on site in designated areas that are isolated from surface drains and banded to contain any spillages.

7.3. Specific end use(s)

Specific end use(s)

Application by brush. Mix with Base component before use. Please refer to the relevant Belzona® Instructions For Use for further information.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

HYDROCARBONS, C9, AROMATICS

Long-term exposure limit (8-hour TWA): SUP 100 mg/m³

Ingredient comments

OEL's are taken from the current version of EH40 except those that are marked 'SUP' which are assigned by the supplier of the substance.

BENZYL ALCOHOL (CAS: 100-51-6)

BELZONA® 3121 (MR7) SOLIDIFIER

DNEL	<p>Industry - Inhalation; Short term systemic effects: 110 mg/m³</p> <p>Industry - Inhalation; Long term systemic effects: 22 mg/m³</p> <p>Industry - Dermal; Short term systemic effects: 40 mg/kg/day</p> <p>Industry - Dermal; Long term systemic effects: 8 mg/kg/day</p> <p>Consumer - Inhalation; Long term systemic effects: 5.4 mg/m³</p> <p>Consumer - Inhalation; Short term systemic effects: 27 mg/m³</p> <p>Consumer - Dermal; Long term systemic effects: 4 mg/kg/day</p> <p>Consumer - Dermal; Short term systemic effects: 20 mg/kg/day</p> <p>Consumer - Oral; Long term systemic effects: 4 mg/kg/day</p> <p>Consumer - Oral; Short term systemic effects: 20 mg/kg/day</p>
PNEC	<p>Fresh water; 1 mg/l</p> <p>Sediment (Freshwater); 5.27 mg/kg</p> <p>marine water; 0.1 mg/l</p> <p>Sediment (Marinewater); 0.527 mg/kg</p> <p>Intermittent release; 2.3 mg/l</p> <p>STP; 39 mg/l</p> <p>Soil; 0.456 mg/kg</p>

HYDROCARBONS, C9, AROMATICS

DNEL	<p>Workers - Inhalation; Long term systemic effects: 150 mg/m³</p> <p>Workers - Dermal; Long term systemic effects: 25 mg/kg/day</p> <p>Consumer - Inhalation; Long term systemic effects: 32 mg/m³</p> <p>Consumer - Dermal; Long term systemic effects: 11 mg/kg/day</p> <p>Consumer - Oral; Long term systemic effects: 11 mg/kg/day</p>
-------------	---

4,4'-METHYLENEBIS(CYCLOHEXANAMINE) (CAS: 1761-71-3)

DNEL	Consumer - Inhalation; Long term systemic effects: 0.5 mg/m ³
-------------	--

2,4,6-tris(dimethylaminomethyl)phenol (CAS: 90-72-2)

DNEL	<p>Workers - Inhalation; Long term systemic effects: 0.13 mg/m³</p> <p>Workers - Inhalation; Short term systemic effects: 0.52 mg/m³</p> <p>Workers - Dermal; Long term systemic effects: 0.15 mg/kg/day</p> <p>Workers - Dermal; Short term systemic effects: 0.6 mg/kg/day</p>
PNEC	<p>Fresh water; 0.084 mg/l</p> <p>marine water; 0.0084 mg/l</p> <p>Intermittent release; 0.84 mg/l</p> <p>STP; 0.2 mg/l</p>

8.2. Exposure controls**Appropriate engineering controls**

Use in well ventilated areas or provide adequate mechanical ventilation. Where reasonably practicable adequate ventilation should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of vapours below the relevant occupational exposure limits, suitable respiratory protective equipment should be worn (see 'Respiratory protection' below).

Eye/face protection

It is recommended that eye protection, for example safety spectacles or goggles are worn at all times during the handling and use of this material. Eye protection should be selected in accordance with EN 166 Personal eye protection.

BELZONA® 3121 (MR7) SOLIDIFIER

Hand protection

Hand protection should be selected in accordance with EN 374 Protective gloves against chemicals. The breakthrough time of the gloves selected should exceed the expected use period. Where this is not possible gloves should be changed in good time, and in any case before the breakthrough time is exceeded. If any doubt exists, advice should be sought from glove suppliers on appropriate types. Barrier creams may help to protect exposed areas of skin but are not substitutes for full physical protection. They should not be applied once exposure has occurred. **SPECIFIC RECOMMENDATIONS** Wear protective gloves made of the following material: Nitrile rubber. Medium-heavy weight gauntlet type gloves that provide wrist protection are suitable.

Other skin and body protection

STANDARD APPLICATIONS Synthetic polyethylene coveralls such as the Tyvek PRO-TECH® or equivalent coveralls manufactured to EN 13034 Type 6, Protective clothing against liquid chemicals. Grossly contaminated clothing should be removed and the skin washed with soap and water or a proprietary skin cleaner. Cotton overalls are normally suitable.

Respiratory protection

Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible. Respirator selection must be based on exposure levels, the hazards of the product and the safe working limits of the selected respirator. It is essential that the concentration of the contaminant(s) in the application environment does not exceed the applicable Occupational Exposure Limit(s) (OELs) multiplied by the Assigned Protection Factor (APF) quoted for the respiratory protective equipment selected. Respiratory protection is not normally required, but the hazards of the Base component should be considered for mixing and application purposes. Respiratory protection is not normally required but it may be required when this product is used in confined spaces or where adequate ventilation cannot be achieved. Where necessary, it is recommended that respiratory protective equipment that complies with EN 136 (full face mask) or EN 140 (half face mask) should be worn in combination with an organic/inorganic vapours, acid gases and ammonia cartridge (ABEK1). Where the application environment is likely to be contaminated by significant concentrations of dust then the appropriate particulate prefilter (N-, R- or, P-series) should be worn in combination with the above. It is essential that the facepiece is correctly fitted and the filter is changed in accordance with the manufacturer's instructions. In confined or poorly-ventilated spaces, a supplied-air respirator must be worn.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Liquid.
Colour	Amber.
Odour	Hydrocarbons.
Odour threshold	Not applicable.
pH	Alkaline.
Melting point	Not available.
Initial boiling point and range	* >155°C/>311°F @ 760 mm Hg
Flash point	55°C/131°F Closed cup.
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	Not applicable.
Vapour pressure	0.43 kPa @ 20°C/68°F

BELZONA® 3121 (MR7) SOLIDIFIER

Vapour density	> 1
Relative density	0.93 - 1.03 @ 20°C/68°F
Solubility(ies)	Partially miscible with water.
Partition coefficient	Not available.
Auto-ignition temperature	Not available.
Decomposition Temperature	Not available.
Viscosity	0.09 - 0.1 P @ 25°C/77°F
Explosive properties	Not applicable.
Oxidising properties	Not applicable.
Comments	*Quoted value relates to solvent content.

9.2. Other information

Other information	This section contains typical values for Health, Safety and Environmental guidance only and is not intended to represent a technical specification for the product.
Volatile organic compound	This product contains a maximum VOC content of 305 g/litre (determined by ASTM D2369-10/D).

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	There are no known reactivity hazards associated with this product.
------------	---

10.2. Chemical stability

Stability	Stable under recommended storage and handling conditions (see Section 7).
-----------	---

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	No hazardous reactions expected when stored and handled as recommended.
------------------------------------	---

10.4. Conditions to avoid

Conditions to avoid	There are no known conditions that are likely to result in a hazardous situation.
---------------------	---

10.5. Incompatible materials

Materials to avoid	Keep away from oxidising agents and strongly acidic materials to prevent the possibility of exothermic reaction.
--------------------	--

10.6. Hazardous decomposition products

Hazardous decomposition products	Does not decompose when used and stored as recommended.
----------------------------------	---

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

Notes (oral LD ₅₀)	Based on available data the classification criteria are not met.
--------------------------------	--

Acute toxicity - dermal

Notes (dermal LD ₅₀)	Based on available data the classification criteria are not met.
----------------------------------	--

Acute toxicity - inhalation

BELZONA® 3121 (MR7) SOLIDIFIER

Notes (inhalation LC₅₀)	Based on available data the classification criteria are not met.
<u>Skin corrosion/irritation</u>	
Animal data	Corrosive to skin.
<u>Serious eye damage/irritation</u>	
Serious eye damage/irritation	Skin corrosive; corrosivity to eyes is assumed. No testing is needed.
<u>Respiratory sensitisation</u>	
Respiratory sensitisation	Based on available data the classification criteria are not met.
<u>Skin sensitisation</u>	
Skin sensitisation	May cause skin sensitisation or allergic reactions in sensitive individuals.
<u>Germ cell mutagenicity</u>	
Genotoxicity - in vitro	Based on available data the classification criteria are not met.
Genotoxicity - in vivo	Based on available data the classification criteria are not met.
<u>Carcinogenicity</u>	
Carcinogenicity	Based on available data the classification criteria are not met.
IARC carcinogenicity	Not listed.
NTP carcinogenicity	Not listed.
<u>Reproductive toxicity</u>	
Reproductive toxicity - fertility	Based on available data the classification criteria are not met.
Reproductive toxicity - development	Based on available data the classification criteria are not met.
<u>Specific target organ toxicity - single exposure</u>	
STOT - single exposure	Respiratory irritant effects that impair function with symptoms such as cough, pain, choking, and breathing difficulties. Central nervous system depression including narcotic effects such as drowsiness, narcosis, reduced alertness, loss of reflexes, lack of coordination and vertigo.
<u>Specific target organ toxicity - repeated exposure</u>	
STOT - repeated exposure	Based on available data the classification criteria are not met.
<u>Aspiration hazard</u>	
Aspiration hazard	Entry into the lungs following ingestion or vomiting may cause chemical pneumonitis. Kinematic viscosity ≤ 20.5 mm ² /s.
Route of exposure	Inhalation Ingestion Skin and/or eye contact
Medical considerations	Skin contact constitutes a pronounced hazard. Persons with a history of skin sensitisation problems should only be employed in processes in which this product is used under appropriate medical supervision.

Toxicological information on ingredients.

BENZYL ALCOHOL

Toxicological effects	May be absorbed through the skin.
<u>Acute toxicity - oral</u>	
Acute toxicity oral (LD₅₀ mg/kg)	1,620.0

BELZONA® 3121 (MR7) SOLIDIFIER

Species Rat

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ dust/mist mg/l) 4.178

Species Rat

PHENOL, METHYLSTYRENATED**Acute toxicity - oral**

Acute toxicity oral (LD₅₀ mg/kg) 2,000.0

Species Rat

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 2,000.0

Species Rat

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ dust/mist mg/l) 4.9

Species Rat

Skin sensitisation

Skin sensitisation Local Lymph Node Assay (LLNA) - Mouse: Sensitising.

4,4'-METHYLENEBIS(CYCLOHEXANAMINE)**Toxicological effects****Acute toxicity - oral**

Acute toxicity oral (LD₅₀ mg/kg) 380.0

Species Rat

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Harmful: danger of serious damage to health by prolonged exposure if swallowed.

Target organs Liver Muscles

2,4,6-tris(dimethylaminomethyl)phenol**Acute toxicity - oral**

Acute toxicity oral (LD₅₀ mg/kg) 2,169.0

Species Rat

SECTION 12: Ecological information

Ecotoxicity There is no data on the product itself. The following information is provided on the basis of the individual component data available.

BELZONA® 3121 (MR7) SOLIDIFIER

12.1. Toxicity

Toxicity Based on the individual component data, is expected to have experimental LC50/EC50/IC50 values between 1 and 10 mg/l in most sensitive species.

12.2. Persistence and degradability

Persistence and degradability Based on the individual component data, the product is not expected to be rapidly biodegradable according to OECD/EC guidelines.

12.3. Bioaccumulative potential

Bioaccumulative potential Based on the individual component data, the product is expected to bioaccumulate.

Partition coefficient Not available.

Ecological information on ingredients.

PHENOL, METHYLSTYRENATED

Partition coefficient log Pow: > 3.6

12.4. Mobility in soil

Mobility There is no data available on the product itself.

Ecological information on ingredients.

PHENOL, METHYLSTYRENATED

Adsorption/desorption coefficient Water - log Koc: > 3.2 @ °C

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment Based on information received from our suppliers no PBT or vPvB substances are intentionally added to this product.

12.6. Other adverse effects

Other adverse effects None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal methods Do not allow into drains or watercourses or dispose of where ground or surface waters may be affected. Controlled wastes include non-hazardous industrial and hazardous chemical wastes. All controlled wastes should be disposed of in accordance with regulations made under the Control of Pollution Act and the Environmental Protection Act. In addition, hazardous chemical wastes should be disposed of in accordance with the Hazardous Waste Regulations. When in doubt, using information provided in this safety data sheet, advice should be obtained from the National regulating agency whether the Hazardous Waste Regulations apply. Refer to information sources listed in Section 16. COMPONENT DISPOSAL TRANSIT PACKAGING: shrink or stretch wrap, boxes and fittings that have not been contaminated with product should be re-used or recycled. UNREACTED PRODUCT and empty uncleaned containers should be disposed of as hazardous chemical waste. REACTED PRODUCT, contaminated mixing boards, spatulas, applicators, brushes, nominally empty containers and mixing bowls- once fully cured- should be disposed of as non-hazardous waste.

BELZONA® 3121 (MR7) SOLIDIFIER

Waste class List of Waste (LoW) code: 08 01 11*. *Hazardous waste pursuant to Directive 91/689/EEC. The LoW code quoted in this section is a general entry. LoW codes should be assigned based on the end use of the product. Where a more specific code is available it should be used in preference to the code given above. Where in doubt refer to the List of Wastes (2000/532/EC Commission Decision), your local licensed waste contractor or the National regulating agency. Refer to information sources listed in Section 16.

SECTION 14: Transport information

General Labelling and packaging requirements may vary with pack and load size. Please refer to the current transport regulations. Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of accident or spillage.

14.1. UN number

UN No. (ADR/RID) 2733

UN No. (IMDG) 2733

UN No. (ICAO) 2733

14.2. UN proper shipping name

Proper shipping name (ADR/RID) Amines, flammable, corrosive, n.o.s. (containing 4,4'-Methylenebis(cyclohexanamine) mixture & Aromatic hydrocarbons)

Proper shipping name (IMDG) Amines, flammable, corrosive, n.o.s. (containing 4,4'-Methylenebis(cyclohexanamine) mixture & Aromatic hydrocarbons)

Proper shipping name (ICAO) Amines, flammable, corrosive, n.o.s. (containing 4,4'-Methylenebis(cyclohexanamine) mixture & Aromatic hydrocarbons)

14.3. Transport hazard class(es)

ADR/RID class 3 (8)

IMDG class 3 (8)

ICAO class/division 3 (8)

14.4. Packing group

ADR/RID packing group III

IMDG packing group III

ICAO packing group III

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

Yes. Labelling requirements will vary with hazardous net quantity. Please refer to the current transport regulations.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not carried in bulk.

SECTION 15: Regulatory information

BELZONA® 3121 (MR7) SOLIDIFIER

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations

The provisions of the Health and Safety at Work Act and the Control of Substances Hazardous to Health Regulations with amendments apply to the use of this product at work. This product may add to the calculation for determining whether a site is within scope of the Control of Major Accident Hazards Regulations. Relevant EU provisions transposed through retained EU law.

EU legislation

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended). Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of chemicals (REACH) (as amended).

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

General information

The information contained within this safety data sheet does not constitute the users own assessment of workplace risks as required by other health and safety legislation. As the specific conditions of use of the product are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant National legislation are complied with. The information contained within this safety data sheet is based on the present state of knowledge and current national legislation. It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications.

Key literature references and sources for data

Provision and Use of Personal Protective Equipment Regulations 1992 (SI 1992: 2932). PPG18: Control of Spillages and fire fighting run-off. HSG51 The storage of flammable liquids in containers. HSG53 The selection, use and maintenance of respiratory protective equipment, as amended. HSG97 A step by step guide to COSHH assessment. HSG140 Safe use and handling of flammable liquids. Working with ADR: An introduction to the carriage of dangerous goods by road. UK ENVIRONMENTAL REGULATING AGENCIES: England and Wales- Environment Agency; Scotland- Scottish Environment Protection Agency (SEPA); Northern Ireland- Environment and Heritage Service.

Classification procedures according to SI 2019 No. 720

Where there is no test data available for the mixture, the classification has been determined based on the individual component hazard data in accordance with EC 1272/2008.

Training advice

For further information please contact your supplier, Belzona consultant or Belzona direct.

Revision comments

REVISION. This safety data sheet has been revised in the following Section(s): 1, 2, 3, 8, 11, 12, 13, 15, Please observe the REVISION DATE. Should you be reading a safety data sheet that is more than 24 months old or have concerns over its validity, please contact your local Belzona consultant or Belzona direct (sds@belzona.com) and the most current information will be sent to you.

Revision date

03/08/2022

Revision

3.4

SDS number

11427

SDS status

English. Approved.

BELZONA® 3121 (MR7) SOLIDIFIER

Hazard statements in full

H226 Flammable liquid and vapour.
H302 Harmful if swallowed.
H304 May be fatal if swallowed and enters airways.
H314 Causes severe skin burns and eye damage.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H373 May cause damage to organs (Liver, Muscles) through prolonged or repeated exposure if swallowed.
H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.