



## SAFETY DATA SHEET BELZONA® 3412 BASE

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

**Product name** BELZONA® 3412 BASE  
**Product number** SN2947, SN2948

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** Peelable coating system for protecting flanges and bolts from corrosion. For industrial use only.  
**Uses advised against** The product should not be used for purposes other than those recommended in the appropriate Instructions For Use (IFU) leaflet.

#### 1.3. Details of the supplier of the safety data sheet

**Supplier** Belzona Polymerics Limited  
Claro Road, Harrogate  
HG1 4DS  
United Kingdom  
+44 1423 567641  
sds@belzona.com

**Manufacturer** Belzona Polymerics Limited  
Claro Road, Harrogate  
HG1 4DS  
United Kingdom  
+44 1423 567641  
sds@belzona.com

#### 1.4. Emergency telephone number

**Emergency telephone** ChemTel: +1 813-248-0585

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification (EC 1272/2008)

**Physical hazards** Not Classified  
**Health hazards** Not Classified  
**Environmental hazards** Not Classified

#### 2.2. Label elements

**Hazard statements** NC Not Classified  
**Precautionary statements** P280 Wear protective gloves, protective clothing and eye protection.

#### 2.3. Other hazards

Based on information received from our suppliers no PBT or vPvB substances are intentionally added to this product.

### SECTION 3: Composition/information on ingredients

**BELZONA® 3412 BASE****3.2. Mixtures**

<b>TRIMETHOXY VINYLSILANE</b>	<b>1-5%</b>
CAS number: 2768-02-7	EC number: 220-449-8
	REACH registration number: 01-2119513215-52

**Classification**

Flam. Liq. 3 - H226  
Acute Tox. 4 - H332

<b>BARIUM ALKYLNAPHTHALENESULFONATE</b>	<b>1-5%</b>
CAS number: 25619-56-1	EC number: 939-718-2
	REACH registration number: 01-2119980986-14-XXXX

**Classification**

Acute Tox. 4 - H302  
Acute Tox. 4 - H332  
Skin Irrit. 2 - H315

<b>NAPHTHA (PETROLEUM), HYDROTREATED HEAVY</b>	<b>1-5%</b>
CAS number: 64742-48-9	EC number: 265-150-3
	REACH registration number: 01-2119457273-39

**Classification**

STOT SE 3 - H335, H336  
Asp. Tox. 1 - H304  
Aquatic Chronic 2 - H411

The full text for all hazard statements is displayed in Section 16.

**SECTION 4: First aid measures****4.1. Description of first aid measures**

<b>General information</b>	In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.
<b>Inhalation</b>	Remove to fresh air. Keep the patient warm and at rest. Give nothing by mouth.
<b>Ingestion</b>	If accidentally swallowed obtain immediate medical attention. Keep at rest. Rinse mouth with plenty of water. Do NOT induce vomiting.
<b>Skin contact</b>	Remove contaminated clothing. Wash skin thoroughly with soap and water or use a proprietary skin cleaner. Do NOT use solvents or thinners. If irritation or inflammation persists, seek medical attention.
<b>Eye contact</b>	Contact lenses should be removed. Irrigate copiously with clean, fresh water for at least 15 minutes, holding the eyelids apart, and seek medical advice.

**4.2. Most important symptoms and effects, both acute and delayed****4.3. Indication of any immediate medical attention and special treatment needed**

**Notes for the doctor** None.

**SECTION 5: Firefighting measures****5.1. Extinguishing media**

## BELZONA® 3412 BASE

**Suitable extinguishing media** Use alcohol-resistant foam, carbon dioxide or dry powder to extinguish.

### 5.2. Special hazards arising from the substance or mixture

**Hazardous combustion products** In a fire, hazardous decomposition products such as smoke, carbon monoxide and carbon dioxide may be produced.

### 5.3. Advice for firefighters

**Protective actions during firefighting** Fire will produce dense black smoke containing hazardous products of combustion. Exposure to decomposition products may be a hazard to health. Appropriate self-contained breathing apparatus may be required. Cool closed containers exposed to fire with water spray. Do not allow run-off from fire fighting to enter drains or watercourses.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions** Exclude non-essential personnel. Avoid contact with skin and eyes.

### 6.2. Environmental precautions

**Environmental precautions** Prevent product entering drains or sewers. If the product enters drains or sewers in large quantities, the local Water Company should be contacted immediately; in the case of contamination of streams, rivers or lakes, the appropriate National regulating agency.

### 6.3. Methods and material for containment and cleaning up

**Methods for cleaning up** Contain and collect spillages with non-combustible absorbent materials e.g. sand, earth, vermiculite, diatomaceous earth and place into a suitable labelled container. Clean surfaces down with a water and detergent mixture. Do not allow spilled product or the associated washings to enter surface water drains or watercourses.

### 6.4. Reference to other sections

**Reference to other sections** For personal protection, see Section 8. For waste disposal, see section 13. For information on National regulating agencies refer to Section 16.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

**Usage precautions** GENERAL Vapours may collect in the container headspace during transit or prolonged storage. Avoid the inhalation of vapour when opening the container. Keep the container tightly closed when not in use. Where possible open containers and mix components in a well ventilated place away from the application area. Avoid skin and eye contact. Smoking, eating and drinking should be prohibited in areas of storage and use. For personal protection see Section 8. Always keep in containers made of the same material as the supply container. Good housekeeping methods and regular safe removal of waste materials should be observed. FIRE/EXPLOSION This product is combustible. Exclude sources of heat, sparks and open flame.

**Advice on general occupational hygiene** Wash at the end of each work shift and before eating, smoking and using the toilet. Ensure eye wash facilities (fountain, bottle, vials, etc.) are readily available. Do not put contaminated articles or equipment e.g. spatulas, applicators, brushes, cloths etc., into pockets. Where necessary, contaminated work clothing and shoes should be removed to prevent cross contamination of surfaces and the risk of inadvertent skin contact and ingestion.

### 7.2. Conditions for safe storage, including any incompatibilities

## BELZONA® 3412 BASE

### Storage precautions

Observe the label precautions. Store between 5 °C and 30 °C unless otherwise stated in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. No smoking. Prevent unauthorised access. Store separately from oxidising agents and strongly alkaline and strongly acidic materials. ENVIRONMENTAL STORAGE PRECAUTIONS Spillage, incorrect storage of chemicals or waste materials or unsuitable disposal activities can result in pollutants seeping through the soil, causing serious harm to groundwater- which is a vital source of drinking water. All wastes, especially liquid wastes, must be securely stored on site in designated areas that are isolated from surface drains and banded to contain any spillages.

### 7.3. Specific end use(s)

#### Specific end use(s)

Application by brush. Mix with Solidifier component before use. Please refer to the relevant Belzona® Instructions For Use for further information.

## SECTION 8: Exposure controls/Personal protection

### 8.1. Control parameters

#### Occupational exposure limits

##### 1-METHOXY-2-PROPANOL

Sk

Long-term exposure limit (8-hour TWA): WEL 100 ppm 375 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 150 ppm 560 mg/m<sup>3</sup>

##### ALUMINIUM OXIDE

Long-term exposure limit (8-hour TWA): WEL 4 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL

Sk = Can be absorbed through the skin.

WEL = Workplace Exposure Limit

#### Ingredient comments

Exposure to chemicals assigned occupational exposure limits (OELs) should be controlled using the most effective and reliable measures, proportional to the health risk, which minimise their escape and spread. All relevant exposure routes should be taken into account.

#### TRIMETHOXY VINYLSILANE (CAS: 2768-02-7)

##### DNEL

Workers - Inhalation; Long term systemic effects: 4.9 mg/m<sup>3</sup>

Workers - Dermal; Long term systemic effects: 0.69 mg/kg/day

Consumer - Inhalation; Long term systemic effects: 1.04 mg/m<sup>3</sup>

Consumer - Inhalation; Short term systemic effects: 93.4 mg/m<sup>3</sup>

Consumer - Oral; Long term systemic effects: 0.3 mg/kg/day

Consumer - Dermal; Long term systemic effects: 0.3 mg/kg/day

Consumer - Dermal; Short term systemic effects: 26.9 mg/kg/day

##### PNEC

Fresh water; 0.34 mg/l

marine water; 0.034 mg/l

Intermittent release; 3.4 mg/l

Sediment (Freshwater); 0.27 mg/kg

Soil; 0.046 mg/kg

STP; 110 mg/l

#### BARIUM ALKYLNAPHTHALENESULFONATE (CAS: 25619-56-1)

##### DNEL

Industry - Dermal; Long term systemic effects: 0.183 mg/kg/day

Industry - Inhalation; Long term systemic effects: 1.29 mg/m<sup>3</sup>

Professional - Dermal; Long term systemic effects: 0.183 mg/kg/day

Professional - Inhalation; Long term systemic effects: 1.29 mg/m<sup>3</sup>

**BELZONA® 3412 BASE**

**PNEC** Fresh water; 0.00018 mg/l  
Sediment (Marinewater); 0.313 mg/kg  
Intermittent release; 0.0018 mg/l  
STP; 10 mg/l  
Soil; 0.624 mg/l

**CI PIGMENT BLACK 11 (IRON III OXIDE) (CAS: 1317-61-9)**

**DNEL** Workers - Inhalation; Long term systemic effects: 10 mg/m<sup>3</sup>  
Workers - Inhalation; Long term local effects: 10 mg/m<sup>3</sup>

**1-METHOXY-2-PROPANOL (CAS: 107-98-2)**

**DNEL** Industry - Inhalation; Short term systemic effects: 553.5 mg/m<sup>3</sup>  
Industry - Inhalation; Short term local effects: 553.5 mg/m<sup>3</sup>  
Industry - Dermal; Long term systemic effects: 183 mg/kg/day  
Industry - Inhalation; Long term systemic effects: 369 mg/m<sup>3</sup>  
Consumer - Dermal; Long term systemic effects: 78 mg/kg/day  
Consumer - Inhalation; Long term systemic effects: 43.9 mg/m<sup>3</sup>  
Consumer - Oral; Long term systemic effects: 33 mg/kg/day  
Workers - Inhalation; Long term systemic effects: 369 mg/m<sup>3</sup>  
Workers - Inhalation; Short term local effects: 553.5 mg/m<sup>3</sup>  
Workers - Dermal; Long term systemic effects: 50.6 mg/kg/day  
General population - Inhalation; Long term systemic effects: 43.9 mg/m<sup>3</sup>  
General population - Dermal; Long term systemic effects: 18.1 mg/kg/day  
General population - Oral; Long term systemic effects: 3.3 mg/kg/day

**PNEC** Fresh water; 10 mg/l  
Sediment (Freshwater); 52.3 mg/kg/day  
marine water; 1 mg/l  
Sediment (Marinewater); 5.2 mg/kg/day  
Intermittent release; 100 mg/l  
STP; 100 mg/l  
Soil; 4.59 mg/kg/day

**ZIRCONIUM OXIDE (CAS: 1314-23-4)**

**DNEL** Workers - Dermal; Long term systemic effects: 15.75 mg/kg/day  
Workers - Inhalation; Long term systemic effects: 5 mg/m<sup>3</sup>  
General population - Oral; Long term systemic effects: 7.9 mg/kg/day  
General population - Inhalation; Long term systemic effects: 2.5 mg/m<sup>3</sup>  
General population - Dermal; Long term systemic effects: 7.9 mg/kg/day

**8.2. Exposure controls****Appropriate engineering controls**

STANDARD APPLICATIONS Use in well ventilated areas or provide adequate mechanical ventilation.

**Eye/face protection**

It is recommended that eye protection, for example safety spectacles or goggles are worn at all times during the handling and use of this material. Eye protection should be selected in accordance with EN 166 Personal eye protection. During subsequent machining, grinding, abrasion or removal of this product appropriate eye protection should be selected according to the type of tools or equipment used.

## BELZONA® 3412 BASE

<b>Hand protection</b>	Hand protection should be selected in accordance with EN 374 Protective gloves against chemicals. The breakthrough time of the gloves selected should exceed the expected use period. Where this is not possible gloves should be changed in good time, and in any case before the breakthrough time is exceeded. If any doubt exists, advice should be sought from glove suppliers on appropriate types. Barrier creams may help to protect exposed areas of skin but are not substitutes for full physical protection. They should not be applied once exposure has occurred. <b>SPECIFIC RECOMMENDATIONS</b> Wear protective gloves made of the following material: Nitrile rubber. <b>STANDARD APPLICATIONS</b> Light weight disposable gloves are normally suitable.
<b>Other skin and body protection</b>	<b>STANDARD APPLICATIONS/SPRAY APPLICATIONS</b> Synthetic polyethylene coveralls such as the Tyvek PRO-TECH® or equivalent coveralls manufactured to EN 13034 Type 6, Protective clothing against liquid chemicals. Grossly contaminated clothing should be removed and the skin washed with soap and water or a proprietary skin cleaner. <b>MANUAL APPLICATION OF SMALL QUANTITIES</b> Cotton overalls are normally suitable.
<b>Respiratory protection</b>	<b>STANDARD APPLICATIONS</b> Respiratory protection is not normally required, but the hazards of the Solidifier component should be considered for mixing and application purposes.

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

<b>Appearance</b>	Liquid.
<b>Colour</b>	Grey. Orange.
<b>Odour</b>	Mild (or faint).
<b>Odour threshold</b>	Not applicable.
<b>pH</b>	Not applicable.
<b>Melting point</b>	Not available.
<b>Initial boiling point and range</b>	Not available.
<b>Flash point</b>	72°C/161.6°F Closed cup.
<b>Evaporation rate</b>	Not available.
<b>Flammability (solid, gas)</b>	Not applicable.
<b>Upper/lower flammability or explosive limits</b>	Not applicable.
<b>Vapour pressure</b>	Not available.
<b>Vapour density</b>	Not available.
<b>Relative density</b>	1.21-1.33 @ 20°C/68°F
<b>Solubility(ies)</b>	Immiscible with water.
<b>Partition coefficient</b>	Not applicable.
<b>Auto-ignition temperature</b>	Not applicable.
<b>Decomposition Temperature</b>	Not available.
<b>Viscosity</b>	Not available.
<b>Explosive properties</b>	Not applicable.
<b>Oxidising properties</b>	Not applicable.

#### 9.2. Other information

## BELZONA® 3412 BASE

**Other information** This section contains typical values for Health, Safety and Environmental guidance only and is not intended to represent a technical specification for the product.

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

**Reactivity** There are no known reactivity hazards associated with this product.

#### 10.2. Chemical stability

**Stability** Stable under recommended storage and handling conditions (see Section 7).

#### 10.3. Possibility of hazardous reactions

**Possibility of hazardous reactions** No hazardous reactions expected when stored and handled as recommended.

#### 10.4. Conditions to avoid

**Conditions to avoid** There are no known conditions that are likely to result in a hazardous situation.

#### 10.5. Incompatible materials

**Materials to avoid** Keep away from oxidising agents and strongly alkaline and strongly acidic materials to prevent the possibility of exothermic reaction.

#### 10.6. Hazardous decomposition products

**Hazardous decomposition products** Does not decompose when used and stored as recommended.

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

##### Acute toxicity - oral

**Notes (oral LD<sub>50</sub>)** Based on available data the classification criteria are not met.

##### Acute toxicity - dermal

**Summary** Based on available data the classification criteria are not met.

##### Acute toxicity - inhalation

**Notes (inhalation LC<sub>50</sub>)** Based on available data the classification criteria are not met.

##### Skin corrosion/irritation

**Skin corrosion/irritation** Based on available data the classification criteria are not met.

##### Serious eye damage/irritation

**Serious eye damage/irritation** Based on available data the classification criteria are not met.

##### Respiratory sensitisation

**Respiratory sensitisation** Based on available data the classification criteria are not met.

##### Skin sensitisation

**Skin sensitisation** Based on available data the classification criteria are not met.

##### Germ cell mutagenicity

**Genotoxicity - in vitro** Based on available data the classification criteria are not met.

**Genotoxicity - in vivo** Based on available data the classification criteria are not met.

##### Carcinogenicity

**Carcinogenicity** Based on available data the classification criteria are not met.

## BELZONA® 3412 BASE

**IARC carcinogenicity** Not listed.

**NTP carcinogenicity** Not listed.

### Reproductive toxicity

**Reproductive toxicity - fertility** Based on available data the classification criteria are not met.

**Reproductive toxicity - development** Based on available data the classification criteria are not met.

### Specific target organ toxicity - single exposure

**STOT - single exposure** Based on available data the classification criteria are not met.

### Specific target organ toxicity - repeated exposure

**STOT - repeated exposure** Based on available data the classification criteria are not met.

## SECTION 12: Ecological information

**Ecotoxicity** There is no data on the product itself. The following information is provided on the basis of the individual component data available.

### 12.1. Toxicity

**Toxicity** Based on the individual component data, the products LC50/EC50/IC50 are expected to be greater than 100 mg/l in most sensitive species.

### 12.2. Persistence and degradability

**Persistence and degradability** This product is not expected to present an environmental hazard under current legislation.

### 12.3. Bioaccumulative potential

**Bioaccumulative potential** This product is not expected to present an environmental hazard under current legislation.

**Partition coefficient** Not applicable.

### 12.4. Mobility in soil

**Mobility** There is no data available on the product itself.

### 12.5. Results of PBT and vPvB assessment

### 12.6. Other adverse effects

**Other adverse effects** None known.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

**General information** All cleaning activities including cleaning of equipment, floors and containers, can produce large volumes of contaminated waste. All cleaning agents used are potentially polluting. Water containing detergents, degreasers or any other cleaning agents must not be allowed to enter the surface water drains or soakaways. All water based cleaning/degreasing operations should be carried out in designated areas away from the surface water system and drained to the foul water system. Where this is not possible the surface water system should be isolated by suitable damming techniques and the contaminated water collected and removed for controlled safe disposal.



## BELZONA® 3412 BASE

<b>Disposal methods</b>	Do not allow into drains or watercourses or dispose of where ground or surface waters may be affected. Controlled wastes include non-hazardous industrial and hazardous chemical wastes. All controlled wastes should be disposed of in accordance with regulations made under the Control of Pollution Act and the Environmental Protection Act. When in doubt, using information provided in this safety data sheet, advice should be obtained from the National regulating agency whether the Hazardous Waste Regulations apply. Refer to information sources listed in Section 16. COMPONENT DISPOSAL TRANSIT PACKAGING: shrink or stretch wrap, boxes and fittings that have not been contaminated with product should be re-used or recycled. REACTED PRODUCT, contaminated spatulas, applicators, and mixing containers- once fully cured- should be disposed of as non-hazardous waste.
<b>Waste class</b>	The waste code classification is to be carried out according to the European Waste Catalogue (EWC). Where in doubt refer to the List of Wastes (2000/532/EC Commission Decision), your local licensed waste contractor or the National regulating agency. Refer to information sources listed in Section 16.

### SECTION 14: Transport information

<b>General</b>	Not classified for transport under current National and International Regulations. Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of accident or spillage.
----------------	--

#### 14.1. UN number

Not applicable.

#### 14.2. UN proper shipping name

Not applicable.

#### 14.3. Transport hazard class(es)

Not applicable.

#### 14.4. Packing group

Not applicable.

#### 14.5. Environmental hazards

#### 14.6. Special precautions for user

Not applicable.

#### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** Not carried in bulk.

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

<b>National regulations</b>	The provisions of the Health and Safety at Work Act and the Control of Substances Hazardous to Health Regulations with amendments apply to the use of this product at work.
-----------------------------	---

## BELZONA® 3412 BASE

<b>EU legislation</b>	<p>Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).</p> <p>Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments. In accordance with Regulation (EC) No 453/2010.</p>
-----------------------	--

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

## SECTION 16: Other information

<b>General information</b>	The information contained within this safety data sheet does not constitute the users own assessment of workplace risks as required by other health and safety legislation. As the specific conditions of use of the product are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant National legislation are complied with. The information contained within this safety data sheet is based on the present state of knowledge and current national legislation. It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications.
<b>Key literature references and sources for data</b>	Provision and Use of Personal Protective Equipment Regulations 1992 (SI 1992: 2932). PPG18: Control of Spillages and fire fighting run-off. HSG53 The selection, use and maintenance of respiratory protective equipment, as amended. HSG97 A step by step guide to COSHH assessment. UK ENVIRONMENTAL REGULATING AGENCIES: England and Wales- Environment Agency; Scotland- Scottish Environment Protection Agency (SEPA); Northern Ireland- Environment and Heritage Service.
<b>Classification procedures according to Regulation (EC) 1272/2008</b>	Where there is no test data available for the mixture, the classification has been determined based on the individual component hazard data in accordance with EC 1272/2008.
<b>Training advice</b>	For further information please contact your supplier, Belzona consultant or Belzona direct.
<b>Revision comments</b>	Revised formulation. Please observe the REVISION DATE. Should you be reading a safety data sheet that is more than 24 months old or have concerns over its validity, please contact your local Belzona consultant or Belzona direct (sds@belzona.com) and the most current information will be sent to you.
<b>Revision date</b>	28/02/2020
<b>Revision</b>	1.0
<b>SDS number</b>	41263
<b>SDS status</b>	English. Approved.
<b>Hazard statements in full</b>	<p>H226 Flammable liquid and vapour.</p> <p>H302 Harmful if swallowed.</p> <p>H304 May be fatal if swallowed and enters airways.</p> <p>H315 Causes skin irritation.</p> <p>H332 Harmful if inhaled.</p> <p>H335 May cause respiratory irritation.</p> <p>H336 May cause drowsiness or dizziness.</p> <p>H411 Toxic to aquatic life with long lasting effects.</p>

# **BELZONA® 3412 BASE**